

ACTUATOR USING FLUID CYLINDER, METHOD OF CONTROLLING THE ACTUATOR, AND CHOKE VALVE DEVICES

Patent number: WO2005045257
Publication date: 2005-05-19
Inventor: HOSHINO KIYOSHI (JP); KAWABUCHI ICHIRO (JP)
Applicant: JAPAN SCIENCE & TECH AGENCY (JP); HOSHINO KIYOSHI (JP); KAWABUCHI ICHIRO (JP)
Classification:
- **international:** **F15B11/042; F15B11/044; F15B11/00;** (IPC1-7): F15B11/06
- **europaean:** F15B11/042C; F15B11/044
Application number: WO2004JP16553 20041108
Priority number(s): JP20030379205 20031107


Cited documents:

JP63254203
JP3204402
JP8093951

[Report a data error here](#)

Abstract of WO2005045257

An actuator using a fluid cylinder capable of providing rigidity to the fluid cylinder such as an air cylinder by a simple structure, a method of controlling the actuator, and choke valve device. The actuator comprises the fluid cylinder (1), the first choke valve device (3), and a second choke valve device (5). The fluid cylinder (1) comprises a cylinder chamber (7) and a piston (12) slidably disposed in the cylinder chamber (7) so as to partition the cylinder chamber (7) into a first chamber (9) and a second chamber (11). The first choke valve device (3) is disposed between a fluid pressure source and the first chamber (9) and the second choke valve device (5) is disposed between the fluid pressure source and the second chamber (11). The choke valves (3) and (5) comprise discharge valve mechanisms capable of varying the openings of the valves thereof.



Data supplied from the **esp@cenet** database - Worldwide